

04 Recessed Spots Adjustable LED>The Mirror Recessed Cylinders

11106T/B/W



6W Adjustable Dark light recessed spot, IP20.

Complete with 135mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The Mirror Recessed Cylinders
Order Code	11106T/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	55mm
Diameter	59mm
Cutout Hole Diameter	52mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes

Electrical Characteristics

Gear

External-Included

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

6W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

Fitting

Input Type

Constant Current

Input Current

135mA

Voltage

40V

Safety Class



Power(Watts)

6W

IP Rating

IP20

Light Source

LED built in

LED Type

COB

LED Brand

Osram

LED Number

1

F Mark




Gear

Gear Type


Led Driver

Input Voltage

220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,4-5,67W
Power Factor	0,5
Constant Current	Yes
Output	135mA
Voltage Range	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C...+50°C
Operating Temp	75°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	480lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Pcs/Carton	50
Barcode	5291889075318
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

