

02 Recessed Spots Fixed LED>The Trimless Mini Range Aluminium

10112BTR/B/W



9W/12W COB LED 2-Step trimless Recessed spot, IP20, for general application. Requires 500mA/700mA constant current driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



89015A



89015AT

Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	The Trimless Mini Range Aluminium
Order Code	10112BTR/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	92mm
Diameter	64mm
Cutout Hole Diameter	70mm
Recessed trimless ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	500mA/700mA
Safety Class	III
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
LED Type	COB

LED Brand

Bridgelux

Завантажено з mamadecor.ua

Cable Length

40cm

F Mark



Illumination Data

Colour Temperature

3000K

Lumen Output

1100lm

Light Efficiency

91,67lm/W

CRI

90

Beam Angle

40°

Illumination Diagram



Dark Light

Yes

Packing Info

Pcs/Carton

48

Barcode

5291889070061

HS Code

9405409900

Certification & Warranty

Warranty

5 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

