

02 Recessed Spots Fixed LED>Floating Ring Range

10112R/B/W



12W Dark Light COB LED recessed spot with interchangeable ring.

Ring must be ordered separately.

Requires 700mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



050162/B



050162/DC



050162/GL



050162/W



89015A



89015AT


Physical Specification

| | |
|----------------------|-----------------------------|
| Item Group | 02 Recessed Spots Fixed LED |
| Family | Floating Ring Range |
| Order Code | 10112R/B/W |
| Colour | Black |
| Material | Die Cast |
| Shape | Circular |
| Height | 97mm |
| Diameter | 85mm |
| Cutout Hole Diameter | 68mm |
| Recessed Ceiling | Yes |
| Depth Required | 110mm |
| Indoor | Yes |
| Outdoor | Yes |
| Adjustable | No |

Electrical Characteristics

Fitting

| | |
|---------------|------------------|
| Input Type | Constant Current |
| Input Current | 700mA |
| Safety Class | III |
| Power(Watts) | 12W |
| IP Rating | IP65 |
| Light Source | LED built in |

| | |
|--------------|---|
| LED Type | COB |
| LED Brand | Bridgelux |
| LED Number | 1 |
| Cable Length | 40cm |
| F Mark |  |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 1100lm |
| Light Efficiency | 91,67lm/W |
| CRI | 90 |
| Beam Angle | 50° |
| Illumination Diagram |  |
| Dark Light | Yes |

Packing Info

| | |
|------------|---------------|
| Box Length | 9cm |
| Box Width | 9cm |
| Box Height | 8,5cm |
| Box Weight | 0.362kg |
| Pcs/Carton | 50 |
| Barcode | 5291889061335 |
| HS Code | 9405413990 |

Certification & Warranty

switch to
one light!

one
LIGHT

