

21 Industrial & Floodlights>The IP65 LED Slim Range PC

38145LA/C



IP65 slim LED fitting .

Stainless steel clips included.

Polycarbonate body and diffuser.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately




050084

Physical Specification

Item Group	21 Industrial & Floodlights
Family	The IP65 LED Slim Range PC
Order Code	38145LA/C
Colour	White
Material	PC
Diffuser Material	PC
Shape	Rectangular
Length	1560mm
Width	55mm
Height	37mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	45W
IP Rating	IP65
Light Source	LED built in
Dimmable	No

Cable Length

50cm

Завантажено з mamadecor.ua

F Mark



Fitting

Input Type

Constant Current

Power(Watts)

45W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Sanan

Gear

Gear Type

Led Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

45W

Power Factor

0,9

Constant Current

Yes

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Plastic

Output Terminal

Connector

Brand

Eaglerise

Illumination Data

Colour Temperature

4000K

Lumen Output

4100lm

Light Efficiency

91,1lm/W

CRI

80

Beam Angle

120°

Завантажено з mamadecor.ua

Illumination Diagram



Packing Info

Pcs/Carton

20

Barcode

5291889051138

HS Code

9405104090

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

