

11 Office &amp; Kitchen&gt;Recessed LED Linear Profiles

38152R/W/C



40W Recessed linear with diffuser, ideal for offices.

Complete with 1000mA driver , 4pcs fixing clips, 4pcs connectors & 2pcs end cups.

Can be connected in line

Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Gallery



## Physical Specification

Item Group

11 Office &amp; Kitchen

Family

Recessed LED Linear Profiles

Order Code

38152R/W/C

Colour

White

Material

Aluminium

Diffuser Material



Plastic

Shape

Rectangular

Length	1210mm
Width	70mm
Height	60mm
Cutout Hole Width	1200mm
Cutout Hole Length	60mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No

## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	36V
Power(Watts)	36W
IP Rating	IP20
Light Source	LED built in

LED Type

SMD 2835

Завантажено з mamadecor.ua

LED Brand

Epistar

LED Number

288

## Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

30-42W

Power Factor

0,95

Constant Current

Yes

1000mA

30-42V

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Metal

Output Terminal

Connector

Brand

ATG

## Illumination Data

Colour Temperature

4000K

Lumen Output

3600lm

Light Efficiency

90lm/W

CRI

90

Illumination Diagram



## Packing Info

Box Weight

2.325kg

Pcs/Carton

12

Barcode

5291889058519

[Завантажено з mamadecor.ua](http://mamadecor.ua)

HS Code

9405409900

## Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

