

04 Recessed Spots Adjustable LED>The 7W COB Range

11107B/W/C



7W recessed adjustable spot LED. Suitable for residential and commercial applications, IP20.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

04 Recessed Spots Adjustable LED

Family

The 7W COB Range

Order Code

11107B/W/C

Colour

White

Material

Die Cast

Shape



Circular

Height


55mm

Diameter	90mm
Cutout Hole Diameter	75mm
Recessed Ceiling	Yes
Depth Required	75mm
Indoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	300mA
Voltage	21V
Safety Class	
Power(Watts)	6,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Epistar

LED Number

1

Завантажено з mamadecor.ua

F Mark



Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

4,2-7,2W

Power Factor

0,5

Constant Current

Yes

300mA

14-24V

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Plastic

Output Terminal

Cable

Brand

Lifud

Protection

Short Circuit and Overload

Illumination Data

Colour Temperature

4000K

Lumen Output

560lm

Light Efficiency

80lm/W

CRI

80

Beam Angle

60°

Illumination Diagram



Packing Info

Box Length

12,5cm

Box Width	6cm
Box Height	11,5cm
Box Weight	0,225Kg
Pcs/Carton	50
Barcode	5291889070931
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Average Lifetime	30000hrs
Weee Directive	Yes

switch to
one light!

one
LIGHT

