

04 Recessed Spots Adjustable LED&gt;The COB Recessed Cylinders

11107C/B/W



7W COB LED recessed adjustable spot, for general lighting applications.

Requires 700mA constant current LED driver.

Complies with standard EN60598-1 and any other specific standards.




## Downloads



## Dimensions



## Gallery



## Must be ordered separately



89015A



89015AT

## Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Recessed Cylinders
Order Code	11107C/B/W
Colour	Black
Material	Die Cast
Shape	Circular
Height	85mm
Diameter	90mm
Cutout Hole Diameter	83mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	2 Directions

## Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	10V
Safety Class	III
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in

LED Type
LED Brand
LED Number
Cable Length
F Mark

COB

Bridgelux

1

40cm



## Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram
Dark Light

3000K

550lm

78,57lm/W

90

36°



Yes

## Packing Info

Box Length
Box Width
Box Height
Pcs/Carton
Barcode
HS Code

10cm

10cm

10cm

36

5291889058397

9405409900

## Certification &amp; Warranty

Warranty

5 Years

[Завантажено з mamadecor.ua](http://mamadecor.ua)

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

