

02 Recessed Spots Fixed LED>The Mirror Dark Light Range

50110H/B/W



10W Dark light recessed spot, IP20.

Complete with 700mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	The Mirror Dark Light Range
Order Code	50110H/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	75mm
Width	75mm
Height	42mm
Cutout Hole Width	68mm
Cutout Hole Length	68mm
Recessed Ceiling	Yes

Depth Required	60mm
Indoor	Yes
Adjustable	No

60mm
Yes
No

Electrical Characteristics

Gear

External-Included



Fitting + Driver



Input Voltage	220-240V
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

220-240V

10W
IP20
LED built in
No

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	12V
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3535
LED Brand	Bridgelux
LED Number	4
F Mark	

Constant Current
700mA
12V

10W
IP20
LED built in
SMD 3535
Bridgelux
4



Gear

Gear Type	Led Driver
Input Voltage	220-240V

Led Driver
220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,7-11,9W
Power Factor	0,5
Constant Current	Yes
700mA	11-17V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C...+45°C
Operating Temp	75°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	700lm
Light Efficiency	70lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Pcs/Carton	40
Barcode	5291889074861
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

