

13 Wall & Ceiling LED>Adjustable Display Spots

12208LA/W/W



2x8W COB LED adjustable ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Adjustable Display Spots
Order Code	12208LA/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	40mm
Diameter	2x78mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes
Adjustable	2 Directions

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	9V
Power(Watts)	2x6,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	2

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,5-6,3W

Power Factor	0,5
Constant Current	Yes
700mA	5-9V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	KEGU

Illumination Data

Colour Temperature	3000K
Lumen Output	2x600lm
Light Efficiency	75lm/W
CRI	80
Beam Angle	25°
Illumination Diagram	

Packing Info

Box Length	18,5cm
Box Width	11,5cm
Box Height	20cm
Box Weight	0.988kg
Pcs/Carton	18
Barcode	5291889058922
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

