

21 Industrial & Floodlights>The IP65 LED Connectable Range Single

38118LC/W



IP65 slim LED connectable fitting .

Stainless steel clips included.

Polycarbonate body and diffuser.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads




Dimensions

43mm



665mm

33mm



Gallery



Must be ordered separately




050084

Physical Specification

| | |
|-------------------|---------------------------------------|
| Item Group | 21 Industrial & Floodlights |
| Family | The IP65 LED Connectable Range Single |
| Order Code | 38118LC/W |
| Colour | White |
| Material | PC |
| Diffuser Material | PC |
| Shape | Rectangular |
| Length | 665mm |
| Width | 43mm |
| Height | 33mm |
| Surface Ceiling | Yes |
| Surface Wall | Yes |
| Indoor | Yes |
| Outdoor | Yes |
| Adjustable | No |
| IK Rating | 8 |

Electrical Characteristics

| | |
|------------------|---|
| Gear | Built In |
| Fitting + Driver | |
| Input Voltage | 100-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 18W |
| IP Rating | IP65 |
| Light Source | LED built in |
| Dimmable | No |

Cable Length

50cm

Завантажено з mamadecor.ua

F Mark



Fitting

Input Type

Constant Current

Power(Watts)

18W

IP Rating

IP65

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Sanan

Gear

Gear Type

Led Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

18W

Power Factor

0,9

Constant Current

Yes

IP Rating

IP20

Safety Class



Dimmable

No

Housing Material

Plastic

Output Terminal

Connector

Brand

Eaglerise

Illumination Data

Colour Temperature

3000K

Lumen Output

1500lm

Light Efficiency

83,33lm/W

CRI

80

Beam Angle

120°

Завантажено з mamadecor.ua

Illumination Diagram



Packing Info

Pcs/Carton

20

Barcode

5291889055457

HS Code

9405104090

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

