

11 Office &amp; Kitchen&gt;LED Linear Profiles Medium size

**38150A/W/W**

40W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with 1000mA driver

Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Gallery




## Accessories



050170



050170C/W




38150E/W

Physical Specification

Item Group	11 Office & Kitchen
Family	LED Linear Profiles Medium size
Order Code	38150A/W/W
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1200mm
Width	70mm
Height	35mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20


Light Source	LED built in
Dimmable	No
Cable Length	300cm
F Mark	

## Fitting

Input Type	Constant Current
Input Current	1000mA
Voltage	36V
Power(Watts)	36W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	288

## Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-42W
Power Factor	0,9
Constant Current	Yes
1000mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	BOKE
Protection	0

Colour Temperature	3000K
Lumen Output	3400lm
Light Efficiency	85lm/W
CRI	90
Beam Angle	120°
Illumination Diagram	
UGR	19

## Packing Info

Box Weight	1.941kg
Pcs/Carton	12
Barcode	5291889062370
HS Code	9405409900

## Certification &amp; Warranty

Warranty	3 Years
Weee Directive	Yes

switch to  
**one light!**

one  
LIGHT

