

New 2022 Edition 2>Downlights Fixed LED

50140BW/W/C



60x60 backlit IP65 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Complete with 950mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Related items




050017



050108



89042L



89050TLD

Physical Specification

Item Group

New 2022 Edition 2

Family

Downlights Fixed LED

Order Code

50140BW/W/C

Colour

White

Material

Aluminium + Steel

Shape



Rectangular


Length

595mm

Width	595mm
Height	35mm
Recessed T-Ceiling	Yes
Depth Required	60mm
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	950mA
Voltage	35,2V
Safety Class	
Power(Watts)	33,44W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

28,5-39,9W

Power Factor

0,9

Constant Current

Yes

950mA

30-42V

IP Rating

IP65

Safety Class



Dimmable

No

Housing Material

Plastic

Output Terminal

Cable

Brand

Yingjiao

Protection

No-Load, Short Circuit

Illumination Data

Colour Temperature

4000K

Lumen Output

4000lm

Light Efficiency

100lm/W

CRI

80

Beam Angle

120°

Illumination Diagram



Packing Info

Pcs/Carton

6

Barcode

5291889071754

Certification & Warranty

Warranty

3 Years

Average Lifetime

50000hours

Weee Directive

Yes

switch to
one light!

one
LIGHT

