

21 Industrial &amp; Floodlights&gt;The Industrial IP65 LED UFO Range Aluminium

**63100N/C**

100W SMD LED Industrial High Bay, IP65.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Gallery



## Physical Specification

Item Group

21 Industrial &amp; Floodlights

Family

The Industrial IP65 LED UFO Range Aluminium

Order Code

63100N/C

Colour

Black

Material

Aluminium

Shape



Circular

Height

160mm

|                   |       |
|-------------------|-------|
| Diameter          | 250mm |
| Surface Ceiling   | Yes   |
| Surface Wall      | Yes   |
| Suspended Ceiling | Yes   |
| Indoor            | Yes   |
| Outdoor           | Yes   |
| Adjustable        | No    |

## Electrical Characteristics

|                  |   |
|------------------|---|
| Gear             | Built In  |
| Fitting + Driver |   |
| Input Voltage    | 220-240V  |
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Safety Class     |  |
| Power(Watts)     | 100W  |
| IP Rating        | IP65  |
| Light Source     | LED built in  |
| Dimmable         | No  |
| Cable Length     | 30cm  |
| F Mark           |  |

|               |                  |
|---------------|------------------|
| Fitting       |                  |
| Input Type    | Constant Current |
| Input Current | 500mA            |
| Voltage       | 190V             |
| Power(Watts)  | 95W              |
| IP Rating     | IP65             |
| Light Source  | LED built in     |
| LED Type      | SMD 2835         |

## Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

90-130W

Power Factor

0,9

Constant Current

Yes

500mA

180-260V

IP Rating

IP65

Safety Class



Brand

Lifud

## Illumination Data

Colour Temperature

4000K

Lumen Output

13000lm

Light Efficiency

130lm/W

CRI

80

Beam Angle

90°

Illumination Diagram



## Packing Info

Pcs/Carton

1

Barcode

5291889067948

HS Code

9405409900

Certification & Warranty

Warranty

5 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

