

16 Decorative > LED Circle Rings

62156C/BBS/W



65W LED Pendant , IP20 suitable for residential and commercial application.

Complete with 1600mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads






Dimensions




Physical Specification

| | |
|-------------------|------------------|
| Item Group | 16 Decorative |
| Family | LED Circle Rings |
| Order Code | 62156C/BBS/W |
| Colour | Brushed Brass |
| Material | Aluminium |
| Shape | Circular |
| Height | 3000mm |
| Diameter | 1270mm |
| Suspended Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |


| Gear | | Built In |
|------------------|--|---|
| Fitting + Driver | | |
| Input Voltage | | 220-240V |
| 50 Hz | | Yes |
| 60 Hz | | Yes |
| Safety Class | |  |
| Power(Watts) | | 65W |
| IP Rating | | IP20 |
| Light Source | | LED built in |
| Dimmable | | No |
| F Mark | |  |

| Fitting | |
|---------------|---|
| Input Type | Constant Current |
| Input Current | 1600mA |
| Voltage | 36V |
| Power(Watts) | 56W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD 2835 |
| LED Brand | Bridgelux |
| F Mark |  |

| Gear | |
|---------------|------------|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 44,8-57,6W |

| | |
|------------------|---|
| Power Factor | 0,9 |
| Constant Current | Yes |
| 1600mA | 28-36V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Brand | BOKE |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 4300lm |
| Light Efficiency | 66,15lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|---------------|---------------|
| Box Weight | 4.600kg |
| Pcs/Carton | 1 |
| Carton Weight | 5,7Kg |
| Barcode | 5291889072386 |
| HS Code | 9405413990 |

Certification & Warranty

switch to
one light!

one
LIGHT

