

21 Industrial &amp; Floodlights&gt;The Industrial IP65 LED UFO Range Aluminium

**63150N/C**

150W SMD LED Industrial High Bay, IP65.

Supplied with dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Related items



050114GA





050114HA

## Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Industrial IP65 LED UFO Range Aluminium
Order Code	63150N/C
Colour	Black
Material	Aluminium
Shape	Circular
Height	170mm
Diameter	270mm
Surface Ceiling	Yes

Surface Wall	Yes
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

## Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	150W
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Dimmer type	1-10V
Cable Length	30cm
F Mark	

Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	190V
Power(Watts)	142,5W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835

## Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

135-195W

Power Factor

0,9

Constant Current

Yes

750mA

180-260V

IP Rating

IP65

Safety Class



Brand

Lifud

## Illumination Data

Colour Temperature

4000K

Lumen Output

19500lm

Light Efficiency

130lm/W

CRI

80

Beam Angle

90°

Illumination Diagram



## Packing Info

Box Weight

2.800kg

Pcs/Carton

1

Barcode

5291889067955

HS Code

9405413990

## Certification &amp; Warranty

switch to  
**one light!**

one  
LIGHT

