

14 Plafo>The LED Slim Plafo Range PC

67370/W/W



25W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	14 Plafo
Family	The LED Slim Plafo Range PC
Order Code	67370/W/W
Colour	White
Material	PC
Shape	Circular
Height	40mm
Diameter	350mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

25W

IP Rating

IP54

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

300mA

Voltage

80V

Power(Watts)

24W

IP Rating

IP54

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Epistar

LED Number

335

F Mark



Gear

Gear Type

Led Driver

Input Voltage

100-240V

50 Hz
60 Hz
Power(Watts)
Power Factor
Constant Current
Output
Voltage Range
IP Rating
Safety Class
Dimmable
Housing Material
Output Terminal

Yes

Yes

18,6-24,8W

0,9

Yes

310mA

60-80V

IP20



No

Plastic

Cable

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Illumination Diagram

3000K

1875lm

85lm/W

80



Packing Info

Box Length
Box Width
Box Height
Box Weight
Pcs/Carton
Barcode
HS Code

36cm

36cm

5cm

1.490kg

10

5291889043096

9405114090

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

