

09 Track Lights&gt;The COB Track Light Range Aluminium

65612NT/B/C



30W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Related items



40001A/B



40002A/B



40003A/B

## Physical Specification

Item Group

09 Track Lights

Family

The COB Track Light Range Aluminium

Order Code

65612NT/B/C

Colour

Black

Material

Aluminium

Shape


Circular


Height

123mm


|               |              |
|---------------|--------------|
| Diameter      | 90mm         |
| Track mounted | Yes          |
| Indoor        | Yes          |
| Adjustable    | 2 Directions |

## Electrical Characteristics


|                  |   |
|------------------|---|
| Gear             | Built In  |
| Fitting + Driver |   |
| Input Voltage    | 220-240V  |
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Safety Class     |  |
| Power(Watts)     | 30W   |
| IP Rating        | IP20  |
| Light Source     | LED built in  |
| Dimmable         | No  |

|               |   |
|---------------|---|
| Fitting       |   |
| Input Type    | Constant Current  |
| Input Current | 750mA   |
| Voltage       | 38V   |
| Safety Class  |  |
| Power(Watts)  | 28,5W   |
| IP Rating     | IP20  |
| Light Source  | LED built in  |
| LED Type      | COB   |
| LED Brand     | Bridgelux   |

|           |            |
|-----------|------------|
| Gear      |            |
| Gear Type | Led Driver |

|                  |   |
|------------------|---|
| Input Voltage    | 220-240V  |
| 50 Hz            | Yes   |
| 60 Hz            | Yes   |
| Power(Watts)     | 25-30W  |
| Power Factor     | 0,9   |
| Constant Current | Yes   |
| 750mA            | 33-40V  |
| IP Rating        | IP20  |
| Safety Class     |  |
| Dimmable         | No  |
| Housing Material | Plastic   |
| Output Terminal  | Connector   |
| Brand            | Lifud   |
| Protection       | Short Circuit Protection  |

#### Illumination Data

|                      |   |
|----------------------|---|
| Colour Temperature   | 4000K   |
| Lumen Output         | 2700lm  |
| Light Efficiency     | 90lm/W  |
| CRI                  | 90  |
| Beam Angle           | 38°   |
| Illumination Diagram |  |

#### Packing Info

|            |               |
|------------|---------------|
| Box Length | 25cm          |
| Box Width  | 10cm          |
| Box Height | 10cm          |
| Box Weight | 1.140kg       |
| Pcs/Carton | 10            |
| Barcode    | 5291889057888 |

Certification & Warranty

Warranty

3 years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

