

19 Wall Recessed &amp; Inground&gt;The Dark Light Inground Range

69070A/W



3,5W COB LED inground uplighter. IP67, stainless steel 316L and die cast aluminium body.

Supplied with non-dimmable LED driver and box for concrete installation.


Complies with standard EN60598-1 and any other specific standards.



## Downloads



## Dimensions



## Gallery



## Physical Specification

Item Group

19 Wall Recessed &amp; Inground

Family

The Dark Light Inground Range

Order Code

69070A/W

Colour

Stainless Steel

Material

Die Cast

Shape



Circular

Height

100mm

Diameter	120mm
Cutout Hole Diameter	100mm
Inground	Yes
Depth Required	120mm+300mm drainage
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	10

## Electrical Characteristics


Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3,5W
IP Rating	IP67
Light Source	LED built in
Dimmable	No
Cable Length	200cm
F Mark	

Fitting	
Input Type	Constant Current
Light Source	LED built in
LED Type	COB
LED Brand	Cree

Gear	
------	--

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power Factor	0,4
Constant Current	Yes
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector

## Illumination Data

Colour Temperature	3000K
Lumen Output	300lm
Light Efficiency	85,7lm/W
CRI	80
Beam Angle	20°
Illumination Diagram	
Dark Light	Yes

## Packing Info

Pcs/Carton	20
Barcode	5291889079668
HS Code	9405413990

## Certification &amp; Warranty

Warranty

2 years

Завантажено з [mamadecor.ua](http://mamadecor.ua)

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

