

13 Wall & Ceiling LED>COB Outdoor Ceiling Cylinders

67380A/W/W



25W COB LED cylinder, IP54, suitable for indoor and outdoor installation.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group

13 Wall & Ceiling LED

Family

COB Outdoor Ceiling Cylinders

Order Code

67380A/W/W

Colour

White

Material

Aluminium

Shape

Circular

Height

160mm

Diameter	120mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics

Gear	Built In
------	----------

Fitting + Driver


Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

Fitting


Input Type	Constant Current
Input Current	600mA
Voltage	38V
Power(Watts)	22,8W
IP Rating	IP54
Light Source	LED built in
LED Type	COB
LED Brand	Osram

Gear

Gear Type	Led Driver
-----------	------------

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18-24W
Power Factor	0,9
Constant Current	Yes
600mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic

Illumination Data

Colour Temperature	3000K
Lumen Output	1800lm
Light Efficiency	72lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	

Packing Info

Box Weight	1.466kg
Pcs/Carton	12
Barcode	5291889044987
HS Code	9405413990

Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

