

21 Industrial & Floodlights > AC LED Floodlights 100-250W

7028CF/B/C



250W AC LED flood light with adjustable mounting bracket.

IP65 rated for outdoor use.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	21 Industrial & Floodlights
Family	AC LED Floodlights 100-250W
Order Code	7028CF/B/C
Colour	Black
Material	Die Cast
Diffuser Material	Glass
Shape	Rectangular
Length	525mm
Width	410mm
Height	57mm
Surface Ceiling	Yes
Surface Wall	Yes

Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Gear	No
------	----

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	250W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	30cm
F Mark	

Illumination Data

Colour Temperature	4000K
Lumen Output	22500lm
Light Efficiency	90lm/W
CRI	80
Beam Angle	110°
Illumination Diagram	

Packing Info

Box Length	34.5cm
Box Width	5.3cm

Box Height	45.5cm
Box Weight	3,4Kg
Pcs/Carton	4
Carton Length	53.8cm
Carton Width	22.8cm
Carton Height	43cm
Carton Weight	13,8Kg
Barcode	5291889056034
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to
one light!

one
LIGHT

