

#####

#####



72### KAEDRA IP65 4#18###
#####

13437

#####

#####	Kaetra
### #####	Weatherproof enclosure
### #####	Enclosure for modular device
Accessories included with enclosure	4 wiring straps 4 terminal blocks 32 holes 2 terminal block supports 4 marking kits
Mounting plate description	Without mounting plate

#####

#####	#####
##### 18 # # #	18
##### ##### 18 #	72
#####	4
#####	### II #####
#####	4 marking kit 4 wiring strap 2 terminal block support 4 terminal block 32 holes
### #####	##### #####
##### # #	89 #
[In] #####	160 #
### #####	DIN
Number of pre-cutouts PG ISO	17
#####	4 # 32
#####	64 x 10 mm ² 64 x 16 mm ²
#####	Optional keylock
#####	self-extinguishing polymer
#####	448 #
#####	842 #
#####	160 #

#####	88 ##
#####	##### transparent green ##### (RAL 7035)
#####	
#####	EN 50262 IEC 60529 IEC 60439-3 IEC 670 EN 50102 IEC 60695-2-1
#####	650 °C # ##### # IEC 60695-2-1
##### IP	IP65 # ##### # IEC 60529
##### ##	IK09 # ##### # EN 50102
Environmental characteristics (UV)	##### ## ## class 3 # ##### # ISO 4582:2010 Ultraviolet degradation test # ##### # ISO 4892-2:2013
#####	II
#####	-25...60 °C
###	
##### 1	PCE
##### # ##### 1	1
##### 1	8,01 ##
##### 1	17 cm
##### 1	47 cm
##### 1	85 cm
### ##### 2	P12
##### # ##### 2	11
##### 2	100,11 ##
##### 2	80 cm
##### 2	80 cm
##### 2	120 cm
#####, ## ##### # #####	
#####	##### Green Premium
##### REACH	##### REACH
REACH free of SVHC	###
##### ## RoHS	##### (##### ## ## ## RoHS) ##### ## RoHS
Toxic heavy metal free	###
## #####	###
##### ##	###
##### RoHS	
##### RoHS #####	China RoHS declaration ##### RoHS # ##### (##### ## ## ## RoHS)
#####	#####
Halogen content performance	Halogen free product

#####

#####

18 months