

### product code

PL-SLIMFRW

### name

Slim Trimless Adjustable, Matt White, Fire Rated, GU10, Plaster-in

### description

Slim Trimless Adjustable FR



### item

|                           |                  |                               |         |
|---------------------------|------------------|-------------------------------|---------|
| <b>finish</b>             | Matt White       | <b>bathroom zones</b>         | N/A     |
| <b>main material</b>      | Steel            | <b>tilt angle</b>             | 15      |
| <b>overall dimensions</b> | dia.125 x 150mm  | <b>adjustable</b>             | tilt    |
| <b>application</b>        | Recessed Ceiling | <b>warranty</b>               | 5 years |
| <b>cut out</b>            | 86mm             | <b>avg hours of operation</b> | N/A     |
| <b>recess depth</b>       | 160              | <b>weight rating</b>          | N/A     |
| <b>fire rated</b>         | Yes              | <b>nett weight</b>            | 0.39    |
| <b>ip rating</b>          | IP20             |                               |         |

### light

|                                 |          |
|---------------------------------|----------|
| <b>light source</b>             | GU10 LED |
| <b>lumen output</b>             | N/A      |
| <b>colour temperature (cct)</b> | N/A      |
| <b>cri</b>                      | N/A      |
| <b>beam angle</b>               | N/A      |
| <b>efficacy (lm/w)</b>          | N/A      |
| <b>lamp detail</b>              | MR16     |
| <b>lamp included?</b>           | No       |

### electrical

|                         |                  |
|-------------------------|------------------|
| <b>maximum wattage</b>  | 10               |
| <b>input power</b>      | 220-240V 50/60Hz |
| <b>driver included?</b> | N/A              |
| <b>power factor</b>     | N/A              |
| <b>switch</b>           | N/A              |
| <b>dimmable</b>         | Yes              |
| <b>dimming method</b>   | N/A              |
| <b>class</b>            | 1 (Earthed)      |
| <b>cable length</b>     | N/A              |

### additional information

Tested to BS476 part 21 in a 30, 60 and 90 minute ceiling  
Plaster skim after installation

# project collection

technical drawings

