


S-TRACK 3-CIRCUIT SURFACE-MOUNTED TRACK DALI




S-TRACK
3-circuit surface mounted track,
DALI, 2m



S-TRACK
3-circuit surface mounted track,
DALI, 2m

Rated voltage	220-250V ~50/60Hz	220-250V ~50/60Hz
Max. perm. current	16A	16A
Mech. max. load	300N	300N
Mech. max. load	30 kg	30 kg
Feed-in capability	no	no
Material	Aluminium	Aluminium
Colour	black	white
Length	200 cm	200 cm
Width	3.6 cm	3.6 cm
Height	3.6 cm	3.6 cm
Weight	1.84 kg	1.84 kg
Item no.	1002631	1002632



S-TRACK
3-circuit surface mounted track,
DALI, 3m



S-TRACK
3-circuit surface mounted track,
DALI, 3m

Rated voltage	220-250V ~50/60Hz	220-250V ~50/60Hz
Max. perm. current	16A	16A
Mech. max. load	300N	300N
Mech. max. load	30 kg	30 kg
Feed-in capability	no	no
Material	Aluminium	Aluminium
Colour	black	white
Length	300 cm	300 cm
Width	3.6 cm	3.6 cm
Height	3.6 cm	3.6 cm
Weight	2.76 kg	2.76 kg
Item no.	1002633	1002634