


COMPENSATION MODULE



Product details


220-240V ~50/60Hz
Material: Plastic PC
L: 9.5 cm Ø: 1.5 cm

Note

Reduces or rectifies dimming problems such as flickering, flashing or if the LED lighting does not go to 100% when it is switched on.
The compensator is always connected downstream of the dimmer or switch and in parallel to the downlight spot or LED driver.

Variant	Item no.
<input checked="" type="checkbox"/> black	1002785

LED DRIVER 350mA | 6W




Product details

220-240V ~50/60Hz
Material: Plastic PC
L: 6.3 cm W: 4 cm H: 2.3 cm
Dimmable: C

Voltage sec.	10-17V DC
Watts from	3.5W
Output up to	5.9W
Power factor	0.9
Temperature protection	110°C

Variant	Item no.
<input type="checkbox"/> white	1002791

LED DRIVER 350mA | 10W




Product details

220-240V ~50/60Hz
Material: Plastic PC
L: 8.5 cm W: 4.1 cm H: 2.2 cm
Dimmable: C

Voltage sec.	17-29V DC
Output current	350mA
Output	10W
Watts from	5.95W
Output up to	10.15W
Power factor	0.9
Temperature protection	110°C

Variant	Item no.
<input type="checkbox"/> white	464140

LED DRIVER 350mA | 15W




Product details

220-240V ~50/60Hz
Material: Plastic PC
L: 8.5 cm W: 4.1 cm H: 2.2 cm
Dimmable: C

Voltage sec.	18-30V DC
Output current	350mA
Watts from	9W
Output up to	15W
Power factor	0.9
Temperature protection	110°C

Variant	Item no.
<input type="checkbox"/> white	1002803

LED DRIVER 500mA | 15W




Product details

220-240V ~50/60Hz
Material: Plastic PC
L: 8.5 cm W: 4.1 cm H: 2.2 cm
Dimmable: C

Voltage sec.	26-43V DC
Output current	500mA
Watts from	9.1W
Output up to	15W
Power factor	0.9
Temperature protection	110°C

Variant	Item no.
<input type="checkbox"/> white	464144

LED DRIVER 700mA | 6W



Product details

220-240V ~50/60Hz
Material: Plastic PC
L: 6.3 cm W: 4 cm H: 2.3 cm
Dimmable: C

Voltage sec.	4.8-8.6V
Output current	700mA
Watts from	3.4W
Output up to	6W
Power factor	0.9
Temperature protection	110°C

Note

Suitable for flush-mounted sockets Ø 60 mm and a min. installation depth of 42 mm

Variant	Item no.
<input type="checkbox"/> white	1002792