


LED DRIVER DALI
250-700mA | 20W inc. strain relief



Product details

220-240V ~50/60Hz
Material: PC
L: 15 cm W: 5.2 cm H: 2.8 cm
Dimmable: 1-10V / Dali

Tip


250/350/500/700mA
Output current can be adjusted using DIP switch

Voltage sec.	6-60V
Wattage of	1.5W
Wattage up to	20W
Thermal protection	110°C
Power factor	0,9

Variant	Item No.
<input type="checkbox"/> white	1002423

Manufacturer:
WeiSen Electronic Co., Ltd

LED DRIVER DALI
250-700mA | 40W inc. strain relief



Product details

220-240V ~50/60Hz
Material: PC
L: 12.3 cm W: 7.9 cm H: 2.4 cm
Dimmable: 1-10V / Dali

Tip


250/350/500/700mA
Output current can be adjusted using DIP switch

Voltage sec.	6-58V
Wattage of	1.5W
Wattage up to	40W
Thermal protection	110°C
Power factor	0,9

Variant	Item No.
<input type="checkbox"/> white	1002424

Manufacturer:
WeiSen Electronic Co., Ltd

LED DRIVER DALI
350-1050mA | 60W inc. strain relief



Product details

220-240V ~50/60Hz
Material: PC
L: 12.4 cm W: 7.9 cm H: 2.2 cm
Dimmable: 1-10V / Dali

Tip


350/500/550/650/700/750/
850/900/1000/1050mA
Output current can be adjusted using DIP switch

Voltage sec.	2-74V
Wattage of	1W
Wattage up to	60W
Thermal protection	110°C
Power factor	0,95

Variant	Item No.
<input type="checkbox"/> white	464032

Manufacturer:
TCI Telecomunicazioni Italia Srl

LED DRIVER DALI
700-1500mA | 50W inc. strain relief



Product details

220-240V ~50/60Hz
Material: PC
L: 12.3 cm W: 7.9 cm H: 2.4 cm
Dimmable: 1-10V / Dali

Tip

700/800/900/1050/1200/1300/1400mA
Output current can be adjusted using DIP switch

Voltage sec.	6-58V
Wattage of	4.2W
Wattage up to	50W
Thermal protection	110°C
Power factor	0,9

Variant	Item No.
<input type="checkbox"/> white	1002425

Manufacturer: WeiSen Electronic Co., Ltd

